

Speedometers (Mech.)



Electro mechanical eddy current principle.
Sturdy mechanism with temperature compensation arrangement.

STANDARD RANGE

S.No.	Part No. Chrome (c)	Part No. Black (b)	φ mm	Range	Type	Please Specify
1	(i) V 10 91 7 c	V 10 91 7 b	140	0-125 Km/h /	K	1) Part Number as required 2) Diameter : 48mm (1 ²⁷ / ₃₂ "), 60mm (2 ³ / ₈ ") 80mm (3 ¹ / ₈ "), 85mm (3 ³ / ₈ ") 100mm (4"), 140mm (5 ¹ / ₂ ") 3) End Fitment :- Square 2.6mm Type Threads K - M18x1.5 U - 5/8"-18UNF N - 14.5φ Snap B - M10x1.0 F - M12x1.0 I - M16x1.0 4) Gear Ratio (W):- 1.0, 0.65 or as required E.g. W=1.0 means 60Km/h Speed at 1000 RPM W=0.65 means 60Km/h Speed at 650 RPM
	(ii) V 10 91 6 c	V 10 91 6 b	100	0-80 MPH		
2	(i) V 10 92 7 c	V 10 92 7 b	140	0-140 Km/h	K	
	(ii) V 10 92 6 c	V 10 92 6 b	100			
3	(i) V 10 52 5 c	V 10 52 5 b	85	0-140 Km/h	K	
	(ii) V 10 52 6 c	V 10 52 6 b	100			
4	V 10 71 4 c	V 10 71 4 b	80	20-160 Km/h	K	
5	V 10 01 1 c	V 10 01 1 b	48	0-60 Km/h	B	

